

2

SECURITY CLASSIFICATION OF THIS PAGE

AD-A259 097



DOCUMENTATION PAGE

Form Approved
OMB No. 0704-0188

2b. DECLASSIFICATION/DOWNGRADING SCHEDULE

1b. RESTRICTIVE MARKINGS

3. DISTRIBUTION/AVAILABILITY OF REPORT

Unlimited

4. PERFORMING ORGANIZATION REPORT NUMBER(S)

DOD POP HMTR/AYD 91-011

5. MONITORING ORGANIZATION REPORT NUMBER(S)

6a. NAME OF PERFORMING ORGANIZATION

Packaging Division, AED

6b. OFFICE SYMBOL
(If applicable)

SMCAR-AEP

7a. NAME OF MONITORING ORGANIZATION

6c. ADDRESS (City, State, and ZIP Code)

U.S. Army, ARDEC
Picatinny Arsenal, NJ 07806-5000

7b. ADDRESS (City, State, and ZIP Code)

This document has been approved
for public release and sale; its
distribution is unlimited.

8a. NAME OF FUNDING/SPONSORING
ORGANIZATION

8b. OFFICE SYMBOL
(If applicable)

9. PROCUREMENT INSTRUMENT IDENTIFICATION NUMBER

8c. ADDRESS (City, State, and ZIP Code)

10. SOURCE OF FUNDING NUMBERS

PROGRAM
ELEMENT NO.

PROJECT
NO.

TASK
NO.

WORK UNIT
ACCESSION NO.

11. TITLE (Include Security Classification)

Performance Oriented Packaging Report for Fuse, Blasting, Time, M700

12. PERSONAL AUTHOR(S)

Sniezek, Frank

13a. TYPE OF REPORT
Final

13b. TIME COVERED

FROM _____ TO _____

14. DATE OF REPORT (Year, Month, Day)

92-11-02

15. PAGE COUNT

16. SUPPLEMENTARY NOTATION

17. COSATI CODES

FIELD

GROUP

SUB-GROUP

18. SUBJECT TERMS (Continue on reverse if necessary and identify by block number)

Performance Oriented Packaging, POP,
Fuse, Blasting, Time, M700,
Mil-B-2427 Wood Box

19. ABSTRACT (Continue on reverse if necessary and identify by block number)

This POP report is for the Fuse, Blasting, Time, M700 which is packaged 4000 feet/ Mil-B-2427 wood box. This report describes the results of testing conducted on a similar packaging which is used as an analogy for this item.

DTIC
ELECTE
DEC 14 1992
S A D

20. DISTRIBUTION/AVAILABILITY OF ABSTRACT

☐ UNCLASSIFIED/UNLIMITED ☐ SAME AS RPT. ☐ DTIC USERS

21. ABSTRACT SECURITY CLASSIFICATION

Unclassified

22a. NAME OF RESPONSIBLE INDIVIDUAL

STEVE RUFFINI

22b. TELEPHONE (Include Area Code)

(201) 724-2515

22c. OFFICE SYMBOL

SMCAR-AEP

II. TITLE: Performance Oriented Packaging Report for Fuse, Blasting,
Time, M700

PERFORMING ACTIVITY: ARDEC

DATE: 2 Nov 92

Accession For	
NTIS CRA&I	<input checked="" type="checkbox"/>
DTIC TAB	<input type="checkbox"/>
Unannounced	<input type="checkbox"/>
Justification	
By	
Distribution	
Availability Codes	
Dist	Avail and/or Special
A-1	

10-10-1944

92-31313

1. DATA SHEET

CONTAINER

Type: Box
UN Code: 4C1
Nomenclature: Box, Packing, Ammunition for Fuse, Blasting, Time, M700
Specification Number: Type II, Grade A, Class 2, Mil-B-2427
Drawing Number: 9242365 (Level A) or 9242367 (CONUS)
Material: Wood
Gross Weight: 107 pounds (Level A)
55 pounds (CONUS)
Outside Dimensions: 30 1/2 x 15 5/16 x 17 7/32 (Level A)
31 5/8 x 15 13/16 x 16 19/32 (CONUS)
Inside Dimensions: 27 3/8 x 13 3/4 x 14 7/8 (Level A)
28 1/2 x 14 1/4 x 14 1/4 (CONUS)

PRODUCT

Name: Fuse, Blasting, Time, M700
Specification Number: Mil-F-45144
United Nations Number: 0105
Physical State: Solid
Amount per Container: 4000 feet

2. BACKGROUND, TESTS, AND RESULTS

Reference the following document:
a. 49CFR, October 1, 1991 Edition

Instead of testing the wooden box containing the actual item, three wooden boxes built to the same specification but packed with a fiberboard box filled with sand were tested. The corresponding weight and dimensions of the tested box are as follows:

Gross Weight: 150 pounds
Outside Dimensions: 31 5/8 x 16 x 17 3/8
Inside Dimensions: 28 1/2 x 14 1/4 x 14 7/8

This falls within the guidelines for analogy IAW Variation III of para. 178.601(g)(3) of Reference a.

A Stacking Test was conducted on one container with a weight of 1600 pounds for 72 hours in lieu of three containers for 24 hours. This weight exceeds the minimum requirement for a 10 foot stack height which is 1036 pounds.

A Loose Cargo Test was conducted on three containers for one hour. The packages were tested at a vibration table frequency such that the bottom of the packages were raised 1/4 inch from the platform, which exceeds the requirement of 1/16 inch.

A Four Foot Drop Test was conducted on one of the containers that was subjected to the Loose Cargo Test. One container was dropped five times at different orientations as follows: top, bottom, long side, short side, and a top corner at the closure. This exceeds the requirement of one drop per container.

Test results indicated no leakage or spillage of the contents from the containers following any of the tests conducted, meeting the requirements of the 49 CFR.